

**TUBULAR CABLE LUG CU, VERSION FOR FINE-STRANDED CONDUCTORS DIN 0295, 240 MM<sup>2</sup> M 16, 1 PIECE**
**Article number: 183366**

Tubular cable lugs Cu. Design for fine stranded conductors according to DIN 0295 and IEC 228. Technical data - Material: Cu-ETP according to DIN EN 13600 - Flared cable entry "Easy Entry"- Surface: electro tin plated, other surfaces on request - Annealed to copper hardness F20. Design: Cross-section: 240 mm<sup>2</sup>; Bolt-Ø: 16 mm; W: 41; Øi: 23; Øe: 28; C1: 19; C2: 21; a: 41; L: 101; Weight per 100 pcs.~kg: 15,66; PU/pc. 1



Length (mm)	100 mm
Width (mm)	41 mm
Height (mm)	32 mm
Weight (kg)	0,15664 kg

Attribute	Value
Connection thread dimension (metric)	16
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	240 mm <sup>2</sup>
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	500 kcmil
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	K1.5 = feindrätig

GTIN: 4021103833667

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de