

## AL COMPRESSION CABLE LUG DIN 46329, 1 PIECE

**Article number: 183646**

AL compression cable lugs DIN 46329, made of E-Al, bare, longitudinally sealed design with oil stop. Design: Cross-section rm/sm: 240 mm<sup>2</sup>; Cross-section se: 300 mm<sup>2</sup>; Pin Ø: M10; Code number: 32; D1: 21 mm; D2: 10.5 mm; A: 70 mm; B: 38 mm; L: 103 mm; Weight per 100 pcs ~kg: 15.5; Crimping 7 mm: 3; Crimping 5 mm: 8; acc. to DIN: -; acc. to PU/pc.: 1

|             |          |
|-------------|----------|
| Length (mm) | 103 mm   |
| Width (mm)  | 38 mm    |
| Height (mm) | 38 mm    |
| Weight (kg) | 0,155 kg |



| Attribute                             | Value                                     |
|---------------------------------------|---|
| Connection thread dimension (metric)  | 10  |
| Number of fixing holes                | 1   |
| Code number                           | 32  |
| Material                              | Aluminium                                 |
| Color                                 | sonstige                                  |
| Nominal cross-section aluminum, RM/SM | 240 mm <sup>2</sup> - 240 mm <sup>2</sup> |
| Suitable for Al/St ropes              | No  |
| Cross-sectional shape                 | rund                                      |
| Longitudinal density                  | Yes                                       |
| Corresponds to DIN                    | Yes                                       |
| Nominal cross-section aluminum, SE    | 300 mm <sup>2</sup> - 300 mm <sup>2</sup> |
| Sleeve shape                          | kurz                                      |
| St nominal cross-section              | - mm <sup>2</sup>                         |

GTIN: 4021103836460

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de