

AL COMPRESSION CABLE LUG DIN 46329, 1 PIECE

Article number: 183653

AL compression cable lugs DIN 46329, made of E-Al, bare, longitudinally sealed design with oil stop. Design: Cross-section rm/sm : 400 mm^2 ; Bolt \varnothing : M12; Code number: 38; D1: 26 mm; D2: 13 mm; A: 73 mm; B: 38 mm; L: 116 mm; Weight per 100 pcs ~kg: 38; Compression 7 mm: 3; Compression 5 mm: -; acc. to DIN: x; acc. to PU/pc.: 1

| | |
|-------------|---------|
| Length (mm) | 116 mm |
| Width (mm) | 38 mm |
| Height (mm) | 38 mm |
| Weight (kg) | 0,38 kg |



| Attribute | Value |
|---------------------------------------|-------------------------|
| Connection thread dimension (metric) | 12 |
| Number of fixing holes | 1 |
| Code number | 32 |
| Material | Aluminium |
| Color | sonstige |
| Nominal cross-section aluminum, RM/SM | 400 mm^2 - 400 mm^2 |
| Suitable for Al/St ropes | No |
| Cross-sectional shape | rund |
| Longitudinal density | Yes |
| Corresponds to DIN | Yes |
| Nominal cross-section aluminum, SE | 500 mm^2 - 500 mm^2 |
| Sleeve shape | kurz |
| St nominal cross-section | - mm^2 |

GTIN: 4021103836538

CIMCO Werkzeuge GmbH & Co. KG
 Hohenagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de