

CRIMP CONNECTOR CU, DIN 46267, PART 1, CONDUCTOR CROSS-SECTION 300 MM², LENGTH 101 MM, 1 PIECE**Article number: 183712**

Crimp connector Cu, DIN 46267, part 1. Technical data; Material: Cu-ETP according to DIN EN 13600; Surface: galvanic, other surfaces on request; for strain-relieved connections; especially suitable for fine-stranded conductors according to IEC 228; Annealed to copper hardness F 20. Design: cross-section: 300 mm²; code number: 32; \emptyset i: 24.5; \emptyset e: 32; L: 101; weight per 100 pcs.~kg: 29.86; compression: 7 mm: 2-2; compression: 5 mm: - PU/pc: 1

Length (mm)	101 mm
Width (mm)	32 mm
Height (mm)	32 mm
Weight (kg)	0,2986 kg



CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de

Attribute	Value
Surface protection	verzinkt
Material	Kupfer
Execution	DIN-Ausführung
Connection type	Stoßverbinder
Suitable for solid conductors	Yes
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Sleeve shape	lang
Insulation	ohne
Nominal cross-section	300 mm ² - 300 mm ²
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Oil stop/center bar	No
Voltage series	bis 35 kV
Number of branches	2
Rated current	- A

GTIN: 4021103837122

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de