

CRIMP CONNECTOR CU, DIN 46267, PART 1, CONDUCTOR CROSS-SECTION 400 MM², LENGTH 151 MM, 1 PIECE**Article number: 183713**

Crimp connector Cu, DIN 46267, part 1. Technical data; Material: Cu-ETP according to DIN EN 13600; Surface: galvanic, other surfaces on request; for strain-relieved connections; especially suitable for fine-stranded conductors according to IEC 228; Annealed to copper hardness F 20. Design: Cross-section: 400 mm²; Code: 38; Øi: 27.5; Øe: 38.5; L: 151; Weight per 100 pcs.~kg: 71.00; Crimp: 7 mm: 3-3; Crimp: 5 mm: -; Packs of: 1



Length (mm)	150 mm
Width (mm)	39 mm
Height (mm)	39 mm
Weight (kg)	0,71 kg

CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de

Attribute	Value
Surface protection	verzinkt
Material	Kupfer
Execution	DIN-Ausführung
Connection type	Stoßverbinder
Suitable for solid conductors	Yes
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Sleeve shape	lang
Insulation	ohne
Nominal cross-section	400 mm ² - 400 mm ²
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Oil stop/center bar	No
Voltage series	bis 35 kV
Number of branches	2
Rated current	- A

GTIN: 4021103837139

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de