

## AL COMPRESSION CONNECTOR DIN 46267, PART 2

### Article number: 183862

AL compression connector DIN 46267, part 2 made of E-Al, bare. For round-pressed sm/se sector conductors. Design: Cross-section rm/sm: 70 mm<sup>2</sup>; Cross-section se: 95 mm<sup>2</sup>; Code number: 18; Inside Ø: 11.2 mm; Length: 10 mm; Weight kg/100: 5.3; Crimping 7 mm: 3-3; Crimping 5 mm: 6-6; PU/unit: 1

Length (mm)	105 mm
Width (mm)	18 mm
Height (mm)	18 mm
Weight (kg)	0,053 kg



Attribute	Value
Material	Aluminium
Nominal cross-section aluminum, RM/SM	70 mm <sup>2</sup> - 70 mm <sup>2</sup>
Suitable for Al/St ropes	No
Cross-sectional shape	rund
Nominal cross-section aluminum, SE	95 mm <sup>2</sup> - 95 mm <sup>2</sup>
For tensile strength connections	No
Oil stop/center bar	No
Suitable for Aldrey ropes	No
Voltage series	0,6/1 kV
Connection as copper bolt	No
Reduced nominal Al cross-section	- mm <sup>2</sup>
Nominal copper cross-section	- mm <sup>2</sup>

GTIN: 4021103838624

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de