


## AL COMPRESSION CONNECTOR DIN 46267, PART 2

**Article number: 183869**

AL compression connector DIN 46267, part 2 made of E-Al, bare. For round pressed sm/se sector conductors. Design: Cross-section rm/sm: 400 mm<sup>2</sup>; Cross-section se: ---; Reader Service Code: 38; Inner Ø: 26 mm; Length: 210 mm; Weight kg/100: 40.8; Compression 7 mm: 4-4; Compression 5 mm: -; Packs of: 1



Length (mm)	210 mm
Width (mm)	38 mm
Height (mm)	38 mm
Weight (kg)	0,408 kg

Attribute	Value
Material	Aluminium
Nominal cross-section aluminum, RM/SM	400 mm <sup>2</sup> - 400 mm <sup>2</sup>
Suitable for Al/St ropes	No
Cross-sectional shape	rund
Nominal cross-section aluminum, SE	500 mm <sup>2</sup> - 500 mm <sup>2</sup>
For tensile strength connections	No
Oil stop/center bar	No
Suitable for Aldrey ropes	No
Voltage series	0,6/1 kV
Connection as copper bolt	No
Reduced nominal Al cross-section	- mm <sup>2</sup>
Nominal copper cross-section	- mm <sup>2</sup>

GTIN: 4021103838693

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de