

## CONNECTION SHRINK SLEEVES FOR 1KV 1.5 - 6/5

**Article number: 184062**

Connection shrink sleeves for compression connectors or screw connectors 1KV. Thick-walled electroshrink joints (heat shrinkable) with excellent mechanical strength, chemical resistance and electrical properties. Inner coating with hot melt adhesive, therefore excellent for protection against water and moisture. For long-term connection of plastic cables in the ground as well as on cable trays or outdoors. Resistant to environmental influences, e.g. UV rays, ozone, oxygen, acids, alkaline earths. Design: Type: 1.5-6/5; Conductor cross-section: 5x1.5 to 6 mm<sup>2</sup>; Cable Ø: 13-21 mm; Hose length: 200x60 mm; Packing unit: 1

Length (mm)	310 mm
Width (mm)	195 mm
Height (mm)	37 mm
Weight (kg)	0,08 kg



Attribute	Value
Length	200 m
Material	Polyolefine (PO-X)
Color	schwarz
Execution	dickwandig
Halogen-free	Yes
Transparent	No
Type	Warmschrumpf
Operating temperature	-25 °C - 155 °C
UL approval	No
Nominal cross-section	1.5 mm <sup>2</sup> - 6 mm <sup>2</sup>
Shrinkage rate	2:1
With inside adhesive	Yes
Inner diameter after shrinkage	13 mm
Inner diameter before shrinkage	21 mm
Printable	Yes
Wall thickness after shrinkage	- mm

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de



GTIN: 4021103840627

CIMCO Werkzeuge GmbH & Co. KG  
Hohenagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de