

CONNECTION SHRINK SLEEVES FOR 1KV 6 - 16/5

Article number: 184064

Connection shrink sleeves for compression connectors or screw connectors 1KV. Thick-walled electroshrink joints (heat shrinkable) with excellent mechanical strength, chemical resistance and electrical properties. Inner coating with hot melt adhesive, therefore excellent for protection against water and moisture. For long-term connection of plastic cables in the ground as well as on cable trays or outdoors. Resistant to environmental influences, e.g. UV rays, ozone, oxygen, acids, alkaline earths. Design: Type: 6-16/5; Conductor cross-section: 5x6 to 16 mm²; Cable Ø: 18-25 mm; Hose length: 450x100 mm; Packing unit: 1



Length (mm)	570 mm
Width (mm)	202 mm
Height (mm)	40 mm
Weight (kg)	0,12 kg

Attribute	Value
Length	450 m
Material	Polyolefine (PO-X)
Color	schwarz
Execution	dickwandig
Halogen-free	Yes
Transparent	No
Type	Warmschrumpf
Operating temperature	-25 °C - 155 °C
UL approval	No
Nominal cross-section	6 mm ² - 16 mm ²
Shrinkage rate	2:1
With inside adhesive	Yes
Inner diameter after shrinkage	18 mm
Inner diameter before shrinkage	25 mm
Printable	Yes
Wall thickness after shrinkage	- mm

CIMCO Werkzeuge GmbH & Co. KG
 Hohenagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de



GTIN: 4021103840641

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de