

TDM 2 SOCKET SLEEVE, DM 6 - 25 MM

Article number: 184762

Mechanical box joint TDM - The mechanical joint is optimally suited as a repair or connection or branch joint due to its quick and easy assembly. The sleeve provides a quick and safe connection of communication, control and supply lines. Waterproof (IP 68), UV-resistant, resistant to alkaline earth and rotting, sleeve body made of impact-resistant plastic, with screw cap, with lug for seal protection against unauthorized access. Suitable for connecting up to four cables. The socket complies with the ÖVE IM22 standard. Scope of delivery: one socket with grommet insert, five cable ties, can of lubricant, cutter, installation instructions. Design: TDM 2: conductor cross-section in mm² passage: 3x1.5 to 5x16 mm²; range of application with Ø from: 6-25 mm; PU: 1.



Length (mm)	280 mm
Width (mm)	90 mm
Height (mm)	75 mm
Weight (kg)	0,422 kg

Attribute	Value
Suitable for	sonstige
Execution	Gießharz
Halogen-free	No
Type	Parallelabzweig
Mining license	No
Nominal conductor cross-section main cable	1.5 mm ² - 16 mm ²
Nominal conductor cross-section branch cable	1.5 mm ² - 16 mm ²
Number of conductors	20
Connection accessories supplied	ohne
Cable diameter of branch cable	6 mm - 25 mm
Cable diameter main cable	6 mm - 25 mm

GTIN: 4021103847626

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de