

## 1 KV TWO-COMPONENT CASTING RESIN SET

### Article number: 184770

1KV two-component casting resin set, as a can container.  
The casting resin complies with the standard according to VDE 0291 Part 2. The polyurethane casting resin is an unfilled, low-viscosity, elastically curing two-component system. Technical data: storable for 24 months; storage in dry rooms between +5°C and +50°C; curing within 24 hours, temperature resistance between -25°C and +120°C in cured state; resin and hardener can be disposed of in household waste. Model: incl. stirring wood, glove and instructions; type: PUR 160-615D; filling quantity/resin: 0.615 kg; filling quantity/hardener: 528cm<sup>3</sup>. PU: 1

|             |          |
|-------------|----------|
| Length (mm) | 225 mm   |
| Width (mm)  | 180 mm   |
| Height (mm) | 111 mm   |
| Weight (kg) | 0,615 kg |



| Attribute                       | Value    |
|---------------------------------|----------|
| Suitable for                    | sonstige |
| Execution                       | Gießharz |
| Halogen-free                    | No       |
| Type                            | sonstige |
| Mining license                  | No       |
| Connection accessories supplied | ohne     |

GTIN: 4021103847701

CIMCO Werkzeuge GmbH & Co. KG  
Hohenagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de