

STAINLESS STEEL CABLE TIES, W X L 12.0 X 680 MM, 25 PIECES, NATURAL**Article number: 186023**

Cable ties made of stainless steel AiSi 316 (DIN 1.4401), with ball lock. Corrosion and radiation resistant, anti-magnetic. Extremely resistant to aggressive chemicals. Steel thickness 0.26 mm (width 4.6/7.9 mm) or 0.32 mm (width 12 mm). Temperature resistance: -80 °C to +538 °C. Certification: UL, DNV, LR. WxL 12.0x680 mm, cable harness max. 203 mm, minimum tensile strength 2200 N

| | |
|-------------|------------|
| Length (mm) | 750 mm |
| Width (mm) | 150 mm |
| Height (mm) | 28 mm |
| Weight (kg) | 0,00615 kg |



CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de

| Attribute | Value |
|-----------------------------------|---------------------|
| Surface protection | unbehandelt |
| Material | Metall |
| Material quality | Edelstahl 316 (V4A) |
| Color | Edelstahl |
| Execution | innenverzahnt |
| Fluorescent | No |
| Halogen-free | Yes |
| Mounting type | sonstige |
| Detectable | Yes |
| Transparent | No |
| Width of the belt | 12 mm |
| Detachable closure | No |
| Labeling area | ohne |
| Strap fastener | Stahlnase |
| Mounting temperature | -10 °C - 80 °C |
| Belt length | 680 mm |
| Operating temperature | -80 °C - 538 °C |
| Bundle diameter | 5 mm - 203 mm |
| Min. holding force | 2200 N |
| UL approval | Yes |
| UV-stable according to ASTM D6779 | Yes |
| Tape thickness | 0.25 mm |

GTIN: 4021103860236

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de