

**STAINLESS STEEL CABLE TIES, W X L 7.9 X 680 MM, 25 PIECES**
**Article number: 186114**

Cable ties made of stainless steel AISI 316 (DIN 1.4401), with ball lock. Corrosion and radiation resistant, anti-magnetic. Extremely resistant to aggressive chemicals. Steel thickness 0.26 mm (width 4.6/7.9 mm) or 0.32 mm (width 12 mm). Additional features of the black version: coating made of polyester, UV-stabilized and halogen-free. Temperature resistance: -80 °C to +538 °C (natural) or -80°C to +538/150°C (black, steel/polyester). Certification: UL, DNV, LR. WxL 7.9x680 mm, cable harness max. 203 mm, minimum tensile strength 1200 N, black coated.



Length (mm)	400 mm
Width (mm)	155 mm
Height (mm)	20 mm
Weight (kg)	0,00325 kg

Attribute	Value
Surface protection	sonstige
Material	Metall
Material quality	Edelstahl 316 (V4A)
Color	schwarz
Execution	innenverzahnt
Fluorescent	No
Halogen-free	Yes
Mounting type	sonstige
Detectable	Yes
Transparent	No
Width of the belt	7.9 mm
Detachable closure	No
Labeling area	ohne
Strap fastener	Stahlnase
Mounting temperature	-10 °C - 80 °C
Belt length	680 mm
Operating temperature	-80 °C - 538 °C
Bundle diameter	5 mm - 203 mm
Min. holding force	1200 N
UL approval	Yes

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de

UV-stable according to ASTM D6779	Yes
Flammability class of the insulating material according to UL94	sonstige
Tape thickness	0.25 mm
VG approval	No
MIL approval	No

GTIN: 4021103861141

CIMCO Werkzeuge GmbH & Co. KG  
Hohenhagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de