

FERRULE INSULATED 1.5 MM²/6 MM, FR DIN, BLACK
Article number: 187011

Insulated wire end ferrules to DIN 46228-4, color series DIN, made of CU-ETP to DIN EN 13600, tin-plated, with polypropylene insulation, suitable for fine-stranded copper conductors of classes 5 and 6 to DIN EN 60228. The ferrules are temperature-resistant up to 105 °C. Technical data: Nominal cross-section (mm²): 1.5 | Insulation color: black | d1: 1.7 | d2: 3.5 | l1: 12 | l2: 6 | S1: 0.15 | S2: 0.25 | Weight per 100 pieces: approx. 0.01 kg | PU/pc: 100.



Length (mm)	12 mm
Width (mm)	3,8 mm
Height (mm)	12 mm
Weight (kg)	0,0001 kg

Attribute	Value
Insulated material	Yes
Surface protection	Kupfer verzinkt
Design	Standard
nominal cross-section	1.5 mm ²
tube length	6 mm
total length	12 mm
Insulation material	Polypropylen (PP)
Halogen-free	Yes
Color	schwarz
For short-circuit-proof cables	No
With identification flag	No
Strip goods	No

GTIN: 4021103112076

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de