

## FERRULE NON-INSULATED 10 MM<sup>2</sup>/12 MM

### Article number: 187443

Uninsulated ferrules made of high-quality copper DHP with a nominal cross-section of 10 mm<sup>2</sup> provide a reliable connection for fine-stranded copper conductors of classes 5 and 6 in accordance with DIN EN 60228. The tin-plated surface with a minimum layer thickness of 3 µm ensures maximum corrosion protection and guarantees a durable, stable electrical connection. The sleeves meet the requirements of DIN 46228-1 and are made of Cu-ETP. Technical data: Nominal cross-section (mm<sup>2</sup>): 10 | d1: 4.5 | d2: 5.8 | L: 12 | s: 0.2 | Weight per 100 pieces: approx. 0.034 kg | PU/unit: 100.



|             |            |
|-------------|------------|
| Length (mm) | 12 mm      |
| Width (mm)  | 5,8 mm     |
| Height (mm) | 12 mm      |
| Weight (kg) | 0,00034 kg |

| Attribute                      | Value              |
|--------------------------------|--------------------|
| Insulated                      | No                 |
| material                       | Kupfer             |
| Surface protection             | verzinnt           |
| Design                         | Standard           |
| nominal cross-section          | 10 mm <sup>2</sup> |
| tube length                    | 12 mm              |
| total length                   | 12 mm              |
| Halogen-free                   | Yes                |
| Color                          | Zinn               |
| For short-circuit-proof cables | No                 |
| With identification flag       | No                 |
| Strip goods                    | No                 |

GTIN: 4021103113752

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de