

WIRE END FERRULE NON-INSULATED 10 MM²/20 MM**Article number: 187446**

Uninsulated ferrules made of high-quality copper DHP with a nominal cross-section of 10 mm² provide a reliable connection for fine-stranded copper conductors of classes 5 and 6 in accordance with DIN EN 60228. The tin-plated surface with a minimum layer thickness of 3 µm ensures maximum corrosion protection and guarantees a durable, stable electrical connection. The sleeves meet the requirements of DIN 46228-1 and are made of Cu-ETP. Technical data: Nominal cross-section (mm²): 10 | d1: 4.5 | d2: 5.8 | L: 20 | s: 0.2 | Weight per 100 pieces: approx. 0.056 kg | PU/unit: 250.



Length (mm)	20 mm
Width (mm)	5,8 mm
Height (mm)	20 mm
Weight (kg)	0,00056 kg

Attribute	Value
Insulated	No
material	Kupfer
Surface protection	verzinnt
Design	Standard
nominal cross-section	10 mm ²
tube length	20 mm
total length	20 mm
Halogen-free	Yes
Color	Zinn
For short-circuit-proof cables	No
With identification flag	No
Strip goods	No

GTIN: 4021103113783

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de