

## WIRE END FERRULE NON-INSULATED 16 MM<sup>2</sup>/32 MM

**Article number: 187453**

Uninsulated wire-end ferrules made of high-quality copper DHP with a nominal cross-section of 16 mm<sup>2</sup> provide a reliable connection for fine-stranded copper conductors of classes 5 and 6 in accordance with DIN EN 60228. The tin-plated surface with a minimum layer thickness of 3 µm ensures maximum corrosion protection and guarantees a durable, stable electrical connection. The sleeves meet the requirements of DIN 46228-1 and are made of Cu-ETP. Technical data: Nominal cross-section ( mm<sup>2</sup>): 16 | d1: 5.8 | d2: 7.5 | L: 32 | s: 0.2 | Weight per 100 pieces: approx. 0.114 kg | PU/unit: 100.



Length (mm)	32 mm
Width (mm)	7,5 mm
Height (mm)	32 mm
Weight (kg)	0,00114 kg

Attribute	Value
Insulated material	No
Surface protection	Kupfer verzinnt
Design	Standard
nominal cross-section	16 mm <sup>2</sup>
tube length	32 mm
total length	32 mm
Halogen-free	Yes
Color	Zinn
For short-circuit-proof cables	No
With identification flag	No
Strip goods	No

GTIN: 4021103113844

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de