

FERRULE NOT INSULATED 35 MM²/18 MM

Article number: 187461

Uninsulated wire-end ferrules made of high-quality copper DHP with a nominal cross-section of 35 mm² provide a reliable connection for fine-stranded copper conductors of classes 5 and 6 in accordance with DIN EN 60228. The tin-plated surface with a minimum layer thickness of 3 µm ensures maximum corrosion protection and guarantees a durable, stable electrical connection. The sleeves meet the requirements of DIN 46228-1 and are made of Cu-ETP. Technical data: Nominal cross-section (mm²): 35 | d1: 8.3 | d2: 11 | L: 18 | s: 0.2 | Weight per 100 pieces: approx. 0.091 kg | PU/unit: 100.



| | |
|-------------|------------|
| Length (mm) | 18 mm |
| Width (mm) | 11 mm |
| Height (mm) | 18 mm |
| Weight (kg) | 0,00091 kg |

| Attribute | Value |
|--------------------------------|--------------------|
| Insulated | No |
| material | Kupfer |
| Surface protection | verzinkt |
| Design | Standard |
| nominal cross-section | 35 mm ² |
| tube length | 18 mm |
| total length | 18 mm |
| Halogen-free | Yes |
| Color | Zinn |
| For short-circuit-proof cables | No |
| With identification flag | No |
| Strip goods | No |

GTIN: 4021103113929

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de