

FERRULE NON-INSULATED 50 MM²/25 MM

Article number: 187468

Uninsulated ferrules made of high-quality copper DHP with a nominal cross-section of 50 mm² provide a reliable connection for fine-stranded copper conductors of classes 5 and 6 in accordance with DIN EN 60228. The tin-plated surface with a minimum layer thickness of 3 µm ensures maximum corrosion protection and guarantees a durable, stable electrical connection. The sleeves meet the requirements of DIN 46228-1 and are made of Cu-ETP. Technical data: Nominal cross-section (mm²): 50 | d1: 10.3 | d2: 13 | L: 25 | s: 0.3 | Weight per 100 pieces: approx. 0.233 kg | PU/unit: 100.



Length (mm)	25 mm
Width (mm)	13 mm
Height (mm)	25 mm
Weight (kg)	0,00233 kg

Attribute	Value
Insulated	No
material	Kupfer
Surface protection	verzinkt
Design	Standard
nominal cross-section	50 mm ²
tube length	25 mm
total length	25 mm
Halogen-free	Yes
Color	Zinn
For short-circuit-proof cables	No
With identification flag	No
Strip goods	No

GTIN: 4021103113998

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de