

TWIST DRILL, HSS-R, 4.2 MM Ø

Article number: 200375

Twist drill, HSS-R according to DIN 338/HSS type N, cylindrical short, right-hand cutting, roll-rolled design. Design: Ø: 4.2 mm; total length: 75; spiral length: 43. PU: 1.

Length (mm)	75 mm
Width (mm)	4 mm
Height (mm)	4 mm
Weight (kg)	0,006 kg

Attribute	Value
Suitable for steel	Yes
Suitable for stainless steel	No
Suitable for plastic	Yes
Total length	75 mm
With centering drill	No
Twist drill	Yes
Thru axle with flat end	No
Suitable for ceramics	No
Suitable for glass	No
Recording system	zylindrische Steckachse
Suitable for non-ferrous metals	Yes
Drill diameter	4.2 mm
With quick-release fastener	No
Number of cutting edges	2
With cooling channel	No
Suitable for tiles	No
Double-sided drill	No
Cutting edge length	43 mm
Suitable for concrete	No
Suitable for stone	No
Suitable for cast iron	No
Suitable for wood	Yes
Shank diameter	4.2 mm
Suitable for drilling	Yes
Cutting direction	rechts

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.

SICHER SEIT 1827.



Cutting material Shank shape Angle of the tip Center drill diameter HSS zylindrisch 118° - mm

GTIN: 4021104003755

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

SICHER SEIT 1827.