

TWIST DRILL, HSS-R, 4.5 MM Ø
Article number: 200379

Twist drill, HSS-R according to DIN 338/HSS type N, cylindrical short, right-hand cutting, roll-rolled design. Design: Ø: 4.5 mm; total length: 80; spiral length: 47. PU: 1.

Length (mm)	80 mm
Width (mm)	4 mm
Height (mm)	4 mm
Weight (kg)	0,007 kg



Attribute	Value
Suitable for steel	Yes
Suitable for stainless steel	No
Suitable for plastic	Yes
Total length	80 mm
With centering drill	No
Twist drill	Yes
Thru axle with flat end	No
Suitable for ceramics	No
Suitable for glass	No
Recording system	zylindrische Steckachse
Suitable for non-ferrous metals	Yes
Drill diameter	4.5 mm
With quick-release fastener	No
Number of cutting edges	2
With cooling channel	No
Suitable for tiles	No
Double-sided drill	No
Cutting edge length	47 mm
Suitable for concrete	No
Suitable for stone	No
Suitable for cast iron	No
Suitable for wood	Yes
Shank diameter	4.5 mm
Suitable for drilling	Yes
Cutting direction	rechts

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Cutting material	HSS
Shank shape	zylindrisch
Angle of the tip	118 °
Center drill diameter	- mm

GTIN: 4021104003793

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de