

HSS STEP DRILL, HSS, 9 DRILL STEPS

Article number: 201201

HSS step drill, especially for cable glands in electrical assembly, perfectly round and cylindrical holes in various diameters, centering, spot drilling, reaming and deburring in one operation, suitable for use in hand-held and pillar drilling machines in trade and industry, for sheets and plates, profiles and pipes made of steel, brass, copper, aluminum, V2A steel, plastic, wood, etc. up to 3 mm thickness. Mounting shank 12 mm Ø. Design: HSS; Drill Ømm: 8.0 center drill; 12.5 through hole for PG7/M12; 15.2 through hole for PG9; 18.6 through hole for PG11; 20.4 through hole for PG 13.5; 22.5 through hole for PG 16; 25.8; 28.3 through hole for PG 21; 30.5 core hole for M32; Drill steps: 9. PU: 1.



Length (mm)	85 mm
Width (mm)	165 mm
Height (mm)	45 mm
Weight (kg)	0,133 kg

Attribute	Value
Max. panel thickness	3 mm
Number of cutting edges	3
With cooling channel	No
Shank diameter	12 mm
Cutting direction	rechts
Cutting material	HSS
Center point	Yes
Spiral groove	No
Carbide version	Yes
With edge breaker	Yes
Number of drilling steps	9
Max. Drill diameter	30.5 mm
Interchangeable centering tip	Yes
Unit of measurement	PG
Min. drilling diameter	8 mm

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de



GTIN: 4021104012016

CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de