

HSS STEP DRILL, HSS-TIN, 12 DRILL STEPS

Article number: 201210

HSS step drill, especially for cable glands in electrical assembly, perfectly round and cylindrical holes in various diameters, centering, spot drilling, reaming and deburring in one operation, suitable for use in hand-held and pillar drilling machines in trade and industry, for sheets and plates, profiles and pipes made of steel, brass, copper, aluminum, V2A steel, plastic, wood, etc. up to 3 mm thickness. Mounting shank 12 mm Ø. After hardening additionally TiN (titanium nitride) coated surfaces are extremely hard and smooth. Higher cutting speed allows faster work, lower wear brings 5 to 10 times longer tool life! Design: HSS-TIN; Drill-Ømm: 8.0 center drill; 12.5 through hole for PG7/M12; 14.5 core hole for M16; 16.5 through hole for M16; 18.5 core hole for M20; 20.5 through hole for M20; 23.5 core hole for M25; 25.5 through hole for M25; 30.5 core hole for M32; 32.5 through hole for M32; 38.5 core hole for PG29; 40.5 through hole for M40; drilling steps: 12. PU: 1.



Length (mm)	84 mm
Width (mm)	46 mm
Height (mm)	162 mm
Weight (kg)	0,25 kg

Attribute	Value
Max. panel thickness	3 mm
Number of cutting edges	3
With cooling channel	No
Shank diameter	12 mm
Cutting direction	rechts
Cutting material	HSS
Center point	Yes
Spiral groove	No
Carbide version	Yes
With edge breaker	Yes
Number of drilling steps	12
Max. Drill diameter	40.5 mm
Interchangeable centering tip	Yes
Unit of measurement	ISO

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de



Min. drilling diameter | 8 mm

GTIN: 4021104012108

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de