

SDS-PLUS HAMMER DRILL PROFIL, 22 MM Ø, TOTAL LENGTH 450 MM

Article number: 208386

SDS-Plus hammer drill PROFIL with carbide cutting edges, high drilling speed due to wide Twinmax helix, the user is protected by vibration-optimized drilling behavior, certified by the Prüfgemeinschaft Mauerbohrer (PGM) requirements of the German Institute for Building Technology (DIBt), fits all machines with SDS- Plus receptacles. Made in Germany; Design: Ø-22 mm; Total length: 450; Spiral length: 400; Packs: 1



Length (mm)	510 mm
Width (mm)	45 mm
Height (mm)	19 mm
Weight (kg)	0,567 kg

Attribute	Value
Suitable for steel	No
Suitable for stainless steel	No
Suitable for plastic	No
Total length	460 mm
With centering drill	No
Twist drill	No
Thru axle with flat end	No
Suitable for ceramics	No
Suitable for glass	No
Recording system	SDS-plus
Suitable for non-ferrous metals	No
Drill diameter	22 mm
With quick-release fastener	Yes
Number of cutting edges	2
With cooling channel	No
Suitable for tiles	No
Double-sided drill	No
Cutting edge length	410 mm
Suitable for concrete	Yes
Suitable for stone	Yes
Suitable for cast iron	No
Suitable for wood	No
Shank diameter	10 mm

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Suitable for drilling	No
Cutting direction	rechts
Cutting material	HM
Shank shape	zylindrisch
Angle of the tip	- °
Center drill diameter	- mm

GTIN: 4021104083863

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de