

## LASER RANGEFINDER

### Article number: 211563

Digital Laser Rangefinder FVP-30, Digital laser rangefinder with protective cover, Measuring range up to 30 m, Measuring accuracy 2 mm/m, Rubberized case, Cover with Beamfinder™ function, LCD display, backlit Distance, area, volume or indirect measurement (via Pythagoras function) Dynamic (continuous) measurement, 2 reference points and 5 units of measurement selectable, Storage of last 20 results, Automatic switch-off laser (20 sec)/device (5 min), Operating temperature -10 to +40°C, Storage temperature -20 to +60°C, Laser class: II, 2x1.5 V AAA batteries included.



Length (mm)	112 mm
Width (mm)	40 mm
Height (mm)	26 mm
Weight (kg)	0,135 kg

Attribute	Value
Interface	No
Measured value memory	No
Length	26 mm
Width	112 mm
Height	40 mm
Weight	0.11 kg
Accuracy	0 mm/m
Visible signal section	No
With remote control	No
Length of the signal section	30 m
Rotating signal section	No
Laser class	Klasse 2
Wavelength of the sensor	- nm

GTIN: 4021103069608

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de